

REEL SEAT EPOXY PASTE

A THICK, PASTE-LIKE, TWO-PART EPOXY FOR BONDING REEL SEATS TO FISHING ROD BLANKS.

PRODUCT DESCRIPTION: Reel Seat Epoxy is a reactive polymer compound adhesive with added ultraviolet protection.

SURFACE PREPARATION: Surface must be clean, free of dirt, oil, and other foreign matter.

APPLICATION: Reel Seat Epoxy must be used with a clean and dry rod. Accurately measure 2 parts A to 1 part B into a clean container. Accurate measurement is very important. Improper measurement of Resin and Hardener will result in a sticky finish. Use in a room where the temperature is between 65° to 90°F. Mix thoroughly by hand with a stir stick for about 2-3 minutes until mixture is completely swirl-free. Universal colorants may be added to mixture for a variety of decorative purposes.

Working time: 40 minutes @ 77°F

Set time: 18-24 hours @ 77°F

Allow to cure for a minimum 48 hours prior to use.

CLEAN UP:

Use Acetone to clean up tools and uncured epoxy. After epoxy has cured, it must be removed mechanically or by chemically stripping. It is advisable to clean immediately after use.

LIMITATIONS:

Material should be stored in a dry place between 65- 80°F and out of the reach of children. Resin and hardener should not be left in an open container. This product should be used within one year of purchase.

WARRANTY: B.D. Classic Enterprises guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller.

USE ONLY WITH ADEQUATE VENTILATION

KEEP OUT OF REACH OF CHILDREN